

PLUSHBOND



Product Description:

PLUSHBOND, a high-density, high-compressive strength, bonded urethane carpet cushion manufactured specifically for use in glue-down cushion installations in high-traffic areas. Polypropylene mesh lamination is applied to the surface of the cushion to make it suitable for gluing to the carpet. This bonds the carpet and cushion together to avoid carpet wrinkling and re-stretch problems common to stretch-in installations, and provides the durable comfort of a cushion under any carpet in commercial applications.

Physical Properties:

| | |
|--|---|
| Construction | Bonded Urethane |
| Color | Purple |
| Weight Class | 8 lbs./cu. ft. |
| CFD @ 65% Deflection (Compression Force Deflection) | 9.56 PSI |
| Roll Size | 25 sq. yds.=225 sq. ft. |
| Roll Length | 37.5 ft. |
| Roll Width | 6 ft. |
| Thicknesses Available | 5/16 in. |
| Lamination | Red Polyethylene with Extra-fine Polypropylene Mesh |
| Ohio Building Code & BOCA ASTM E-84 (Tunnel Test) | Class II Building Material |
| Flame Spread | 65 |
| Fuel Contribution | 15 |
| Smoke Density | 80 |
| Recommended Traffic | Heavy Duty Residential Extra-Heavy Commercial (3/8" Max) |
| FHA Certification | UM-72a Class II Installations (1/4" Min) |

Warranty: *Gold Seal Lifetime Warranty*

Scottdel warrants this product to be free of manufacturing defects and will replace defective cushion, free of charge, for the life of the original carpet under which it is installed. This warranty is valid only if the cushion is installed in accordance with industry standards, and covers both cushion and replacement costs.cushion

SCOTCDEL
400 Church Street
Swanton, Ohio 43558-1199
Customer Service: 1.800.446.2341
www.scottdel.com

updated 1/23/02